



POWER AUTO TRANSMISSION FLUID A AUTO TRANSMISSION FLUID

POWER AUTO TRANSMISSION FLUID A is a transmission fluid, having a low co-efficient of friction to meet specific equipment manufacturers' requirements.

PERFORMANCE STANDARDS: General Motors Type A Suffix A
TES – 122 of Detroit Diesel Allison
TEML 03 of ZF, Germany
DBL-6623-10 of Daimler Benz, Germany

CHARACTERISTICS	POWER AUTO TRANSMISSION FLUID A
Kinematic Viscosity @ 100°C, cSt	7.4 – 7.9
Viscosity index, min	160
Flash point, COC, °C, min	180
Pour point, °C, max	(-) 39

APPLICATION:

- **POWER AUTO TRANSMISSION FLUID A** is recommended for automotive transmission and power steering units of automobiles and light trucks requiring Type A Suffix A fluids and also synchromesh gears.

PERFORMANCE BENEFITS:

- Compatible with all types of seal materials
- Suitable for all seasons
- High oxidation stability
- Long service life
- Good anti-wear and anti-corrosive properties
- Good anti-foam characteristics

(Version # 1 April 14th 2008)

Disclaimer: APAR makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility.