



POWER COOL REFRIGERATION COMPRESSOR OILS

POWER COOL OILS are premium grade Refrigeration Compressor lubricants blended from highly refined naphthenic base oils having excellent oxidation stability.

PERFORMANCE STANDARDS: BIS: 4578-1989
Carrier Corporation, USA - PP 46 –I

CHARACTERISTICS	POWER COOL		
	32	46	68
ISO VG	32	46	68
Kinematic Viscosity @ 40°C, cSt	33-35	43-46	63-65
Flash point, COC, °C, min	154	160	170
Pour point, °C, max	-30	-27	-24

APPLICATION:

- Recommended for lubrication of wide range of refrigeration compressors operating with conventional refrigerants except sulphur dioxide and Freon.
- Suitable for lubrication of reciprocating and rotary compressors.
- Low pour point and excellent low temperature fluidity of the product make them excellent choice for sub zero application temperatures.

PERFORMANCE BENEFITS:

- Good fluidity at very low temperature
- Good oxidation stability
- Good thermal stability
- High condenser efficiency
- Suitable for both Reciprocating and Rotary compressors
- Resist deposit formation during use

(Version # 1 April 14th 2008)

Disclaimer: APAR makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility.