



POWER CYL 460 & 680 CYLINDER OIL

POWERCYL oils are straight cylinder oils manufactured from premium performance cylinder oil base stocks. These oils have good film strength and thermal degradation characteristics.

PERFORMANCE STANDARDS: BIS 2297 - 1997

CHARACTERISTICS	POWER CYL	
	460	680
ISO VG	460	680
Kinematic Viscosity, cSt @ 40°C	420 - 480	640-680
	@ 100°C	28 - 32
Viscosity Index, min	90	85
Flash point, COC, °C, min	280	280
Pour point, °C, max	0	0

APPLICATION:

- Recommended for lubrication of cylinders of steam engines.
- Ideal product for lubrication of heavily loaded slow speed worm gears.
- Recommended for lubrication of paper and textile mill calendar bearings and sugar mill roller bearings

PERFORMANCE BENEFITS:

- Enables higher loading of equipment due to its high load carrying ability
- Reduces wear of cylinder walls and piston rings
- Good corrosion and rust protection
- Reduces deposit formation at high temperatures
- Excellent adhesive property, which helps to resist water washing

(Version # 1 April 14th 2008)

Disclaimer: APAR makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility.