



POWER TRANSMISSION FLUID F10 TRANSMISSION FLUID

POWER TRANSMISSION FLUID F10 is specially formulated with selected base oils and additive packages.

PERFORMANCE STANDARDS: Ford ESW-M2C-33F

CHARACTERISTICS	POWER TRANSMISSION FLUID F10
SAE	10
Colour	Red
Kinematic Viscosity @ 100°C, cSt	7.2 – 7.8
Viscosity index, min	150
Flash point, COC, °C, min	180
Pour point, °C, max	(-) 39

APPLICATION:

- **POWER TRANSMISSION FLUID F10** is suitable for applications requiring transmission fluid meeting Ford ESW-M2C-33F specification.

PERFORMANCE BENEFITS:

- Compatible with all types of rubber seal materials
- Suitable for all seasons
- High oxidation stability
- Long service life
- Good anti-wear and anti-corrosive properties
- Good anti-foam characteristics
- Ensures excellent shift feel
- Reduces maintenance cost due to prevention of transmission damage
- Prevents wear of gear pumps and other parts

(Version # 1 April 14th 2008)

Disclaimer: APAR makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility.