



POWER TURBO PREMIUM TURBINE BEARING LUBRICANTS

POWER TURBO OILS are blended from premium highly refined, hydro-treated base stocks with well researched selected anti-oxidant, rust inhibitor and anti-foam additive package.

PERFORMANCE STANDARDS:	BIS:1012-1987 (Reaffirmed 1993)	British Standard BS 489:1983
	U.S. Military MIL-L-17672D	German Standard DIN 51515
	Brown Boveri HT GD 90 117E	General Electric GEK-28143 A
	Alstom Atlantique NBA P50001	General Electric GEK-46506 B
	CEGB 207001	General Electric GEK-141003H
	U.S.Steel 120 and 125 (Bench Test)	

CHARACTERISTICS	POWER TURBO		
	32	46	68
ISO VG	32	46	68
Kinematic Viscosity @ 40 °C, cSt	28-33	42-48	64-72
Viscosity index, min	100	98	98
Flash point, COC, °C, min	190	200	210
Pour point, °C, max	-9	-6	-6
TAN mg KOH/gm	0.1	0.1	0.1
Rust test (D-665 A & B 24 hrs)	Pass	Pass	Pass
Air release value @ 50 °C, minutes,	3	4	6

* Non-standard grades like **Power Turbo –57 & 100**: Available on request.

APPLICATION:

- Recommended for lubrication of steam, hydraulic and gas turbines.
- Suitable for hydraulic systems requiring lubricant with excellent anti-oxidation characteristics.
- Recommended for lubrication of turbo-compressors.

PERFORMANCE BENEFITS:

- Excellent demulsibility
- Excellent ability to release entrained air
- Thermally stable
- Good rust and corrosion protection
- Long service life

(Version # 1 April 14th 2008)

Disclaimer: APAR makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility.