

CERTIFIED HI-LUBE 32, 46, 68, 100

High Performance Single Grade Hydraulic Oil

HI-LUBE Hydraulic Oils are highly refined high viscosity index mineral oils fortified with the following additives...

- Extreme pressure
- Anti-wear
- Anti-oxidation
- Anti-corrosion
- Anti-foam

They are recommended for circulation systems and other enclosed systems like bearings and gears of general machinery.

These Products conform to BIS:10522-83 / BIS 11656-86 and DIN 51524 Part 2 specifications

Provides Superior Equipment Protection for:

- Industrial Manufacturing
- Steel Mills & Foundries
- Paper mills, printing, & packaging
- Construction, Mining
- Excavation & Demolition
- Utility Construction




 **Highly Resistant to Oxidation**

 **Controls Water and Other Contaminants**

 **Controls Foaming**

 **Prevents Rust and Corrosion**

 **Prevents Pump and Cylinder Wear**

 **Ideal for Use With Vane Pumps, Piston Pumps, Gear Pumps**

Physical Properties	ISO 32	ISO 46	ISO 68	ISO 100
Specific Gravity:	0.872	0.874	0.87	0.875
Flash Point: °C	200	210	210	210
Viscosity cSt. @ 40 °C	29.0 - 34.0	44.0 - 51.0	65.0 - 74.0	90.0 - 110.0
Viscosity Index	> 95	> 95	> 95	> 95
Cu-strip corrosion	1 Max	1 Max	1 Max	1 Max
Pour Point ° C	-6	-6	-6	-6