

STRATA LUBE-15W-40

Multipurpose Diesel Engine Oil

DESCRIPTION

Strata Lube 15W-40 is a premium quality, API certified, commercial multipurpose diesel engine oil. The oil is designed for the most severe performance requirements of modern, highly rated turbo charged diesel engines in the over the road transport fleet applications and also off highway operations. It assures outstanding protection against high temperature engine deposits, oil degradation, oil thickening and corrosion resistance. The oil is having excellent shear stability to maintain viscosity under severe, high temperature operations.

PERFORMANCE BENEFITS

- Reduced engine scuffing and bore polishing.
- High engine cleanliness.
- Maximum protection from wear and deposits.
- Suitable for mixed fleet operation.
- Easier cold starting.
- Excellent all weather performance due to improved cold weather properties.
- •Catalytic Converter compatible.

APPLICATION

Strata lube 15W-40 is recommended for new generation commercial diesel vehicles of both American and European design such as Caterpillar and Cummins operating on Heavy duty on-highway and off-highway equipments.





PERFORMANCE STANDARDS

API CF4 / SG, MB 228.1, MIL-L-2104E, MIL-L-46152E, MACK EO-K 2, MAN 271, VOLVO VDS, Volkswagon VW 505 issue 11/92, Allison C4 , Cummins CES 20075

CHARACTERISTICS

SAE GRADE	15W-40
Kinematic Viscosity, cSt @ 100°C	14.0 – 15.0
Viscosity Index, Min.	135
TBN, mg KOH/g	9.5 – 11.5
Flash Point, (COC)°C, Min.	200
Pour Point °C, Max.	(-) 24